

Special Construction Products

WEBAC® Contact Adhesive



Range of application

- Gluing of WEBAC® Polymer Swelling Tape and WEBAC® Bentonite Swelling Tape


Properties

- Flexible
- Ready to use in cartridge
- Fast curing
- Good adhesion also to wet surfaces

Test certificate

- National Test Certificate for WEBAC® Polymer Swelling Tape and WEBAC® Bentonite Swelling Tape in combination with WEBAC® Contact Adhesive

Example



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical data

	Values	
Density, 23 °C	≈ 1.4 g/cm ³	
Skin forming time at 50% air moisture	23 °C	≈ 5 min
Curing time, at 3.5 mm layer thickness, at 50% air moisture	23 °C	≈ 24 h
Application temperature	5 °C up to 40 °C	
Tensile strength • Elongation at break	≈ 3.0 MPa (N/mm ²) • ≈ 300%	
E modulus	≈ 1.6 MPa (N/mm ²)	

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products. © WEBAC-Chemie GmbH. Version 06/2026

Special Construction Products

WEBAC® Contact Adhesive

Product data	
Consumption depending on substrate	≈ 3–10 m per cartridge
Delivery form	Unit 290 ml
Storage	• Between 5 °C and 25 °C • Protected from moisture • In original, sealed containers

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac.de.

Waste disposal

In Germany, empty containers can be disposed of via "Interzero Circular Solutions Germany GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Disposal Notes" in our product catalog or www.webac.de and the safety data sheets.

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de