

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

WEBAC PURseal M ACC3
Accelerator

1.2 Relevant identified uses of the substance or mixture and uses advised against

Restricted to professional users.

Relevant identified uses

accelerator

1.3 Details of the supplier of the safety data sheet

supplier

WEBAC-Chemie GmbH
Fahrenberg 22 Telephone: +49 40 670570
22885 Barsbüttel Telefax: +49 40 6703227
Germany

Department responsible for information

E-mail (competent person) msds@webac.de

1.4 Emergency telephone number

Giftinformationszentrum-Nord

Emergency telephone number: +49 551 192 40
available 24h/365days; Information will be provided in German and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Acute Tox. 4 oral; Acute toxicity; H302 Harmful if swallowed.

Eye Dam. 1; Serious eye damage/eye irritation; H318 Causes serious eye damage.

Skin Corr. 1C; Skin corrosion/irritation; H314 Causes severe skin burns and eye damage.

Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS05 GHS07

Signal word

Danger

Hazard statements

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

P260 Do not breathe vapours.
P280 Wear protective gloves and eye protection/face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER.

Hazard components for labelling

2,2' -oxybisethanol
2-[2-(dimethylamino)ethoxy]ethanol
N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine

Supplemental hazard information

not applicable

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

accelerator

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
* 111-46-6 203-872-2 603-140-00-6	2,2' -oxybisethanol 01-2119457857-21-xxxx Acute Tox. 4 H302 ATE (oral): = 1,120 mg/kg ATE (dermal): = 13,300 mg/kg ATE (inhalative): > 4.6 mg/L (4 h)	25,0 <= 50,0
* 1704-62-7 216-940-1 -	2-[2-(dimethylamino)ethoxy]ethanol 01-2119976346-26-xxxx Acute Tox. 4 H312 / Skin Corr. 1C H314 / Eye Dam. 1 H318 ATE (dermal): 1,663 mg/kg ATE (oral): > 2,150 mg/kg ATE (inhalative): > 392.2 mg/m ³ (4 h)	2,50 <= 10,0
* 189253-72-3 470-720-1 -	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine 01-0000019735-62-xxxx Acute Tox. 4 H302 / Skin Corr. 1B H314 / Skin Sens. 1 H317 / Eye Dam. 1 H318 ATE (oral): > 1,000 mg/kg	1,00 <= 2,50
* 280-57-9 205-999-9 -	1,4-diazabicyclooctane 01-2119980944-22-xxxx Flam. Sol. 1 H228 / Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 ATE (dermal): > 2,000 mg/kg ATE (oral): 700 mg/kg ATE (inhalative): > 20 mg/L (1 h)	1,00 <= 2,50

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

* Avoid contact with skin, eyes and clothes. Avoid breathing spray.

Personal protection equipment: see section 8

Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons.
 Smoking is forbidden.

Always keep in containers that correspond to the material of the original container. Store carefully closed containers upright to prevent any leaks. Do not empty containers with pressure - no pressure vessel!

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.
 Do not store together with: Food and feedingstuffs

Storage class LGK8A - Combustible corrosive substances

Further information on storage conditions

* Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
111-46-6	2,2' -oxybisethanol	-	100 / - (-) mg/m ³

Additional information

Long-term: Long-term occupational exposure limit value

short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
* 280-57-9	1,4-diazabicyclooctane	DNEL long-term inhalative (systemic)	1.2 mg/m ³
* 280-57-9	1,4-diazabicyclooctane	DNEL acute inhalative (systemic)	3.6 mg/m ³
111-46-6	2,2' -oxybisethanol	DNEL long-term inhalative (local)	60 mg/m ³
111-46-6	2,2' -oxybisethanol	DNEL long-term inhalative (systemic)	44 mg/m ³
111-46-6	2,2' -oxybisethanol	DNEL long-term dermal (systemic)	43 mg/kg
* 1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term dermal (systemic)	2.33 mg/kg bw/day
* 1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (local)	1.07 mg/m ³
* 1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	DNEL long-term inhalative (systemic)	0.48 mg/m ³
* 189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	DNEL long-term dermal (systemic)	0.83 mg/kg bw/day
* 189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	DNEL acute dermal, short-term (systemic)	2.49 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
280-57-9	1,4-diazabicyclooctane	PNEC aquatic, intermittent release	1 mg/L
* 280-57-9	1,4-diazabicyclooctane	PNEC aquatic, freshwater	0.1 mg/L
* 280-57-9	1,4-diazabicyclooctane	PNEC aquatic, marine water	0.01 mg/L
280-57-9	1,4-diazabicyclooctane	PNEC sewage treatment plant (STP)	200 mg/L

*	280-57-9	1,4-diazabicyclooctane	PNEC sediment, marine water	0.13 mg/kg
*	280-57-9	1,4-diazabicyclooctane	PNEC sediment, freshwater	1.3 mg/kg
*	280-57-9	1,4-diazabicyclooctane	PNEC soil, freshwater	0.19 mg/kg
	111-46-6	2,2' -oxybisethanol	PNEC aquatic, intermittent release	10 mg/L
*	111-46-6	2,2' -oxybisethanol	PNEC sewage treatment plant (STP)	199.5 mg/L
	111-46-6	2,2' -oxybisethanol	PNEC aquatic, freshwater	10 mg/L
	111-46-6	2,2' -oxybisethanol	PNEC aquatic, marine water	1 mg/L
*	111-46-6	2,2' -oxybisethanol	PNEC sediment, freshwater	20.9 mg/kg
*	111-46-6	2,2' -oxybisethanol	PNEC soil, freshwater	1.53 mg/kg
	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, intermittent release	1 mg/L
*	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, marine water	0.01 mg/L
*	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC aquatic, freshwater	0.1 mg/L
	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sewage treatment plant (STP)	100 mg/L
*	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC sediment, freshwater	0.087 mg/kg
*	1704-62-7	2-[2-(dimethylamino)ethoxy]ethanol	PNEC soil, freshwater	0.028 mg/kg
*	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC aquatic, marine water	0.015 mg/L
*	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC aquatic, freshwater	0.15 mg/L
	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC sewage treatment plant (STP)	10 mg/L
*	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC sediment, marine water	0.054 mg/kg
*	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC sediment, freshwater	0.54 mg/kg
*	189253-72-3	N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine	PNEC soil, freshwater	0.03 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)
 Thickness of the glove material \geq 0.4 mm
 Breakthrough time \geq 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.
 Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166
 Wear closely fitting protective glasses in case of splashes.

Body protection

Wear suitable protective clothing. Change contaminated, saturated clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	colourless
Odour	characteristic
pH	not applicable
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	> 101 °C
flammability	not applicable
Lower explosion limit at 20°C	not determined
Upper explosion limit at 20°C	not determined
Vapour pressure at 20°C	3.529 mbar
Relative vapour density	not applicable
Density at 20 °C	1.1 kg/l
Water solubility at 20°C	partially soluble
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	not determined
Decomposition temperature	not determined
Viscosity at 20 °C:	> 20.5 mm ² /s
particle characteristics	not applicable

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2 Chemical stability

Stable under recommended storage and handling conditions.
Please note the expiry date.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Protect from moisture. Avoid high temperatures or direct sunlight.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO₂), Carbon monoxide, smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

* ATEmix: (oral) 1,325.256 mg/kg

* 1,4-diazabicyclooctane

LD50: dermal (Rabbit): > 2,000 mg/kg

* LD50: oral (Rat): 700 mg/kg

LC50: inhalative (Rat): > 20 mg/L (1 h)

* **2,2' -oxybisethanol**

LD50: oral= 1,120 mg/kg

* LD50: dermal (Rabbit): = 13,300 mg/kg

* LC0: inhalative (Rat): > 4.6 mg/L (4 h)

* **2-[2-(dimethylamino)ethoxy]ethanol**

LD50: dermal (Rabbit): 1,663 mg/kg; (OECD 402)

* LD50: oral (Rat): > 2,150 mg/kg

* LC50: inhalative (Rat): > 392.2 mg/m³ (4 h)

* **N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine**

LD50: oral (Rat): > 1,000 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

* **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

Algae toxicity

* **1,4-diazabicyclooctane**

ErC50: > 180 mg/L (72 h)

* **2,2' -oxybisethanol**

NOEC (Scenedesmus quadricauda): = 2,700 mg/L (8 d)

* **2-[2-(dimethylamino)ethoxy]ethanol**

ErC50: (Selenastrum capricornutum): 160 mg/L (72 h)

Method: OECD 201

* **N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine**

ErC50: (Selenastrum capricornutum): = 64 mg/L (72 h)

NOEC (Pseudokirchneriella subcapitata): = 32 mg/L (72 h)

Daphnia toxicity

1,4-diazabicyclooctane

EC50 > 100 mg/L (48 h)

* **2,2' -oxybisethanol**

EC50 (Daphnia magna (Big water flea)): > 10,000 mg/L (48 h)

* **2-[2-(dimethylamino)ethoxy]ethanol**

EC50 (Daphnia magna (Big water flea)): > 100 mg/L (48 h)

Method: OECD 202

N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine
EC50 (Daphnia magna (Big water flea)): > 100 mg/L (48 h)

Fish toxicity

1,4-diazabicyclooctane

LC50: = 100 mg/L (96 h)

* **2,2' -oxybisethanol**

LC50: (Pimephales promelas (fathead minnow)): = 75,200 mg/L (96 h)

* **2-[2-(dimethylamino)ethoxy]ethanol**

LC50: (Leuciscus idus (golden orfe)): 320 mg/L (96 h)

N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine

LC50: (Cyprinus carpio (Common Carp)): > 100 mg/L (96 h)

12.2 Persistence and degradability

2,2' -oxybisethanol

Biodegradation = 92 % (28 d)

12.3 Bioaccumulative potential

2,2' -oxybisethanol

Bioconcentration factor (BCF), (Leuciscus idus (golden orfe)) = 100

Partition coefficient: n-octanol/water = 1

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080409* - Waste adhesives and sealants containing organic solvents or other dangerous substances

Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

UN 2735

14.2 UN proper shipping name

Land transport (ADR/RID)

AMINE, FLÜSSIG, ÄTZEND, N.A.G (enthält 2-(2-(DIMETHYLAMINO)ETHOXY)ETHANOL, N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine))

Sea transport (IMDG)

* Amines, liquid, corrosive, n.o.s. (contains 2-(2-(DIMETHYLAMINO)ETHOXY)ETHANOL, N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine))

Air transport (ICAO-TI / IATA-DGR)

* Amines, liquid, corrosive, n.o.s. (contains 2-(2-(DIMETHYLAMINO)ETHOXY)ETHANOL, N-[2-[2-(dimethylamino) ethoxy] ethyl]-N-methyl-1,3-propanediamine))

14.3 Transport hazard class(es)

Land transport (ADR/RID)	8
Sea transport (IMDG)	8
Air transport (ICAO-TI / IATA-DGR)	8

14.4 Packing group

Land transport (ADR/RID)	III
Sea transport (IMDG)	III
Air transport (ICAO-TI / IATA-DGR)	III

14.5 Environmental hazards

Land transport (ADR/RID)	not applicable
Sea transport (IMDG)	not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

Tunnel restriction code: E
Limited quantity (LQ): 5 ltr
Hazard identification number (Kemler No.): 80

Sea transport (IMDG)

Segregation group: IMDG-Code segregation group 18 - Alkalis
EmS-No.: F-A, S-B
Limited quantity (LQ): 5 ltr

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 376 g/l

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H228	Flammable solid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 oral	Calculation method.
Eye Dam. 1	Calculation method.
Skin Corr. 1C	Calculation method.
Skin Sens. 1	Calculation method.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL: Occupational Exposure Limit Value
BLV: Biological limit values
CAS: Chemical Abstracts Service
CLP: Classification, Labelling and Packaging
CMR: Carcinogenic, Mutagenic and Reprotoxic
DIN: German Institute for Standardization / German industrial standard
DNEL: Derived No-Effect Level
EAKV: European Waste Catalogue Directive
EC: Effective Concentration
EC: European Community
EN: European Standard
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code: International Maritime Code for Dangerous Goods
ISO: International Organization for Standardization
LC: Lethal Concentration
LD: Lethal Dose
:
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Cooperation and Development
PBT: persistent, bioaccumulative, toxic
PNEC: Predicted No Effect Concentration
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
UN: United Nations
VOC: Volatile Organic Compounds
vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.